



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
38.75 CX	±0.09	3	0.5	90%	25.00	+0/-0.025	H-K9L	517642	4.50	±0.10
Plano	-	3	0.5	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: OPTICAL GLASS H-K9L
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 75.00 $\pm 1\%$
7. SURFACE QUALITY : 40-20 SCRATCH-DIG
8. CHAMFER EDGES: 0.5×45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE: 1.0' MINUTES MAX
10. COATING: S1 & S2: Ravg 0.8% @ 400-950nm @ 0° AOI

UNLESS OTHERWISE SPECIFIED:				NAME	DATE				
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN	Sylvia Lin	10.4.24	TITLE: DIAMETER 25.00MM, EFL 75.00MM, H-K9L, VIS-NIR1 COTAED, PLANO-CONVEX LENS				
		CHECK	Eva Du	10.8.24					
		ENG APPR.							
		MFG APPR.							
INTERPRET GEOMETRIC TOLERANCING PER:	QA	Ann Chen	12.18.24	COMMENTS			SIZE	DWG.NO.	REV
MATERIAL H-K9L							A	L-PX0040075025	C
FINISH									
DO NOT SCALE DRAWING	PROJECT NO.				SCALE:	WEIGHT:	SHEET 1 OF 1		