



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
90.53 CX	±0.22	3	0.5	90%	50.00	+0/-0.025	H-K9L	517642	7.00	±0.10
Plano	-	3	0.5	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: OPTICAL GLASS H-K9L
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 175.00 $\pm$ 1%
7. SURFACE QUALITY : 40-20 SCRATCH-DIG
8. CHAMFER EDGES: 0.5 $\times$ 45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE: 1.0' MINUTES MAX
10. COATING: S1 & S2: Ravg<0.5% @1050-1700nm @ 0°AOI

							
UNLESS OTHERWISE SPECIFIED:			NAME				DATE
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN	Sally Song	9.26.24	TITLE: DIAMETER 50.00MM, EFL 175.00MM, H-K9L, NIR 2 COATED, PLANO-CONVEX LENS		
		CHECK					
		ENG APPR.					
		MFG APPR.					
INTERPRET GEOMETRIC TOLERANCING PER:		QA	Ann Chen	12.18.24	SIZE DWG.NO. REV A L-PX0060175050 0		
MATERIAL H-K9L		COMMENTS					
FINISH							
DO NOT SCALE DRAWING		PROJECT NO.			SCALE:	WEIGHT:	SHEET 1 OF 1