

RADIUS	R TOL	POWER	IRRG	CA
131.75 CX	±0.33	3	2.0	90%
Plano	-	5	2.0	90%

DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
101.60	+0.05/-0.10	H-K9L	517642	14.10	±0.20





SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: OPTICAL GLASS H-K9L
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 254.00±1%
7. SURFACE QUALITY : 80-50 SCRATCH-DIG
8. CHAMFER EDGES: 1.0×45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE: 3.0-5.0 MINUTES MAX
10. COATING: UNCOATED

		NAME	DATE
UNLESS OTHERWISE SPECIFIED:	DRAWN	Sally Song	6.26.25
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05	CHECK		
	ENG APPR.		
	MFG APPR.		
INTERPRET GEOMETRIC TOLERANCING PER:	QA		
MATERIAL H-K9L	COMMENTS		
FINISH			
DO NOT SCALE DRAWING	PROJECT NO.		

CLZ OPTICAL
MANUFACTURER FROM CHINA

TITLE:
DIAMETER 101.60MM, EFL 254MM, H-K9L PLANO CONVEX LENSES

SIZE	DWG.NO.	REV
A	L-PX10106	0

SCALE:	WEIGHT:	SHEET 1 OF 1