

RADIUS	R TOL	POWER	IRRG	CA
776.38 CX	±1.94	5	1	90%
776.38 CX	±1.94	5	1	90%

DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
100.00	+0/-0.10	H-K9L	517642	8.20	±0.10





SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: GRADE B, FA PER MIL-G-174, CDGM OR EQUIVALENT, ROHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 750mm±2%
7. SURFACE QUALITY : 60-40 SCRATCH-DIG
8. CHAMFER EDGES: 0.5×45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE:3.0' MINUTES MAX
10. COATING:NONE

		NAME	DATE
UNLESS OTHERWISE SPECIFIED:	DRAWN	Sally Song	03.26.25
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05	CHECK		
	ENG APPR.		
	MFG APPR.		
INTERPRET GEOMETRIC TOLERANCING PER:	QA	Ann Chen	01.18.25
MATERIAL H-K9L	COMMENTS		
FINISH			
DO NOT SCALE DRAWING	PROJECT NO.		

CLZ OPTICAL
MANUFACTURER FROM CHINA

TITLE:

DIAMETER 100MM, EFL 750MM, H-K9L BICONVEX LENS

SIZE	DWG.NO.	REV
A	L-DX10005	0

SCALE:	WEIGHT:	SHEET 1 OF 1